BELT CONVEYOR WORKSHET

Customer		Contact		
		Date	_//	
STYLE:				
Horizontal	X A° L	Undercarriage	H	
Quantity: Model No: Describe application: Fixed Conveyor Portable Conveyor Explain Portable Requirements (if applicable)		L,X Conveyor Length: L Horizontal Length: X Incline Length: A Degree of Incline: Floor Distance: E Infeed Height to Top of Belt: H Discharge Height to Top of Belt:		
Hydraulic Voltage: 115V Single Phase 230V Single Phase 230V Three Phase Other Controls: Start/Stop	Gas Engine 460V Three Phase 208V Three Phase 575 V Three Phase VFD variable speed None		☐ 6" high Side Skirts ☐ Infeed Hopper ☐ Discharge Chute ☐ Support Legs ☐ Drip Pan r pertinent information	
MATERIAL SPECIFICATIONS Product(s) Being Conveyed Minimum/Maximum Product Size % of Fines Present Product Density Product Wt. Ea	Product Wt./Hr. Maximum Surge load Any liquids Present _ Product Temperature Method of Loading _	dat infeed_	Hours/Day of Op Operating Cycle Continous or Inte	pact on Belterationermittenters_



7 www.redlineconveyors.com 34 email: Info@redlineconveyors.com